



February 20, 2021

Subject: Planned Phase-out of Dymax Blue Wave LED Flood

To Our Valued Customers:

Dymax introduced our Blue Wave LED Flood several years ago. In that time, we have brought tremendous innovation to LED flood curing with our All-in-One AX 550 and will bring even more with our high intensity FX 1250 floods.

Our AX-550 offers an All-in-One design with the emitter and power supply combined into a single unit. This unique design reduces the overall footprint of the unit by nearly 30%, while making it a true plug & play item. The small footprint and ease of installation make it beneficial for benchtop users, as well as integrators installing it into larger machines. The FX 1250 will push the boundary of intensity from a flood lamp with LED, providing over $2W/cm^2$ for some wavelengths.

As those products will bring new and unique value to our customers, Dymax will formally phase out the Blue Wave LED Flood from our portfolio. Production and sale of the Blue Wave LED Flood will be discontinued at the end of 2021. Dymax Territory Managers and Application Engineering are available to work with customers to help them with the transition to newer units. For customers with an installed base of Blue Wave LED Floods, we will continue to service and support those units. We recognize customers utilize our equipment for years after purchase and our policy is to service and support our equipment for at least 10 years after we stop producing units. We appreciate your understanding in this matter and our Territory Managers and Application Engineering staff stand ready to answer any questions you have and support you through this transition.

Sincerely,

A handwritten signature in black ink, appearing to read "J. Tomei".

Jason Tomei

Global Product Manager - Equipment

www.dymax.com

Americas

USA | +1.860.482.1010 | info@dymax.com

Europe

Germany | +49 611.962.7900 | info_de@dymax.com
Ireland | +353 21.237.3016 | info_ie@dymax.com

Asia

Singapore | +65.67522887 | info_ap@dymax.com
Shanghai | +86.21.37285759 | dymaxasia@dymax.com
Shenzhen | +86.755.83485759 | dymaxasia@dymax.com
Hong Kong | +852.2460.7038 | dymaxasia@dymax.com
Korea | +82.31.608.3434 | info_kr@dymax.com

©2020 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by, Dymax Corporation, U.S.A.

Technical data provided is of a general nature and is based on laboratory test conditions. Dymax does not warrant the data contained in this bulletin. Any warranty applicable to the product, its application and use, is strictly limited to that contained in Dymax's standard Conditions of Sale. Dymax does not assume responsibility for test or performance results obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by someone other than Dymax or act as a grant of license under any Dymax Corporation Patent. Dymax recommends that each user adequately test its proposed use and application before actual repetitive use, using the data contained in this bulletin as a general guide.